

METEOR 700S

Weather Radar





Technical Data

Mode	Doppler, Dual Polarization
Operating Frequency Range	2700 – 2900 MHz (S-Band)
Typical Operational Range/ Technical Range	400 km / 600 km
Maximum Doppler Velocity	± 214 m/s
System Phase Stability	≤ 0.15°
Transmitter Type	Coaxial Magnetron with solid state, IGBT-switched modulator
Peak Power	850 KW
Noise Figure (Total Receiver)	≤ 2.0dB

METEOR 700S Weather Radar

The METEOR 700S sets the benchmark in weather radar technology for Meteorological Services with special emphasis on long-range surveillance and extreme precipitation in tropical regions.

The METEOR 700S combines cutting-edge technologies with straight-forward and reliable implementation. It features an S-Band magnetron transmitter with a 2nd generation solid-state modulator, a digital receiver, a high-precision antenna and Rainbow® 7, the most uptodate software package for meteorological users.

METEOR 700S Highlights

- High-end Doppler weather radar with unparalleled price-performance ratio
- Proven magnetron technology
- Graceful degradation modulator
- Wide dynamic range receiver, based on Dynrex dual-channel implementation
- Compliant with EU Radio Equipment Directive (RED) due to proprietary high-power filter technology
- · Minimization of lifecycle costs due to high reliability
- Improved range resolution and scanning speed through multi-trip echo recovery
- S-Band advantage: Optimized for long-range surveillance under conditions of extreme precipitations

This publication is issued to provide outline information only and is supplied without liability for errors or omissions. No part of it may be reproduced or used unless authorized in writing. We reserve the right to modify or revise all or part of this document without notice.



