

LEONARDO Germany GmbH

SKIRON^{3D®} doppler lidar system





TECHNICAL DATA

Basic Figure of Merit FOM	> 120 mJ • sqrt(Hz)
Velocity accuracy	0,1 m/s
Laser Beam Quality (M ²)	< 1.2
Operational Range (LOS)	> 20 km 1 s accumulation
	time (normal atmospheric
	conditions)
Radial Wind Speed Range	± 70 m/s
Scanner Pointing Accuracy	± 0.05°
Rotation Speed of Scanning	2°/s to 50°/s during operation

SKIRON3D® **DOPPLER LIDAR SYSTEM**

The SKIRON^{3D®} lidar is the optimal solution for measuring winds and detecting wind hazards. Wind shear, gusts, turbulence, and microbursts are dangerous wind phenomena, which impact airport efficiency and flight safety. SKIRON $^{3D^{\circledast}}$ provides the tools necessary to monitor the hazardous winds threatening airports.

The SKIRON^{3D®} is a coherent pulsed Doppler lidar system, which employs a MOPA (Master-Oscillator-Power-Amplifier) configuration. A multi-channel technique is utilized that allows the combination of high-power and an all-fiber setup. This enables optimal beam quality and long-range measurements.

 ${\rm SKIRON^{3D^{\circledast}}}$ is optimally suited for integration with weather radar for observing 3D wind shear along the glide slope and departure path.

This publication is issued to provide outline information only and is supplied without liability for errors or omissions. No part of it may be reproduced or used unless authorized in writing. We reserve the right to modify or revise all or part of this document without notice.

© Copyright LEONARDO Germany GmbH 2025-06-1-14

leonardogermany.com

SKIRON3D® **HIGHLIGHTS**

- High-end lidar in a cost-effective and modular design, supporting e.g. flexible cooling strategies (global effects of climate change)
- Full remote surveillance and control capability based on Ravis® maintenance tool
- Proprietary scanner design without slip rings
- Air-knife no-contact optical window cleaning
- Integrated camera for lidar northing using the sun, moon. or a fixed target
- Feedback-controlled laser power for long-term stability
- Minimal lifecycle costs due to highly reliable fiber technology
- · Laser operated at eye-safe wavelength

