


M425

MKIIA AND MODE S IFF TRANSPONDER



The M425 equipment is part of a family of MkIIA (MkXII + Mode 5) equipment developed under the NGIFF program in order to provide a state of the art IFF capability. Military identification is available with Mode 4 and Mode 5, supported by an embedded crypto module entirely designed by the company and qualified by NATO Authorities (SECAN).

Compatibility with the latest ATC standards is provided by a Mode S (up to Enhanced Surveillance) that includes an ADSB-OUT capability. Operation in Mode 5 has been successfully verified during bilateral IT-US interoperability trials with the US Navy. Variants of the equipment can be provided for non-NATO applications with a M4-only or National Secure Mode capability.

The equipment has been designed for all applications including avionic (fixed or rotary wings) and ships. The transponder is packed in a rugged single LRU intended for hard mounting, that has the popular for-factor of APX 100. Integration with the platform can be via 1553 Bus, ARINC 429 or RS485; a conventional Control Panel (M910) is available for legacy applications.

The M425 is currently installed on many Italian MoD aircraft, helicopters and ships, and used on a number of NATO platforms. A variant of the equipment, with limited repackaging, is provided for use on the Typhoon aircraft for the needs of the Four Nations.

MAIN FEATURES

- Full MkXII, Mode 5 and Mode S capability
- Embedded crypto certified by SECAN
- Tested for interoperability with US Navy
- Compliant to STANAG 4193, Ed2
- ADSB-OUT capability
- Multiple, self-configuring system interfaces
- Wide operational deployment

OPERATION

The equipment is fully solid-state and of modular construction to facilitate maintenance. Replies are transmitted on two RF connectors to provide full diversity operation, supported by a receive section that provides two matched channels. Multiple options are available in order to interface the Host platform; all interfaces are available in the same unit and are automatically selected at power-up.

These options are:


- MIL-STD-1553 to interface an avionic bus
- RS 485 to interface an FMS or dedicated Control Panel
- ARINC 429 to interface an FMS

SEA SURVEILLANCE

For integration on legacy platforms that do not include a Data Bus or FMS a Control Panel (M910) has been developed; it has the same footprint of existing MkXII panels in order to facilitate aircraft upgrade. For Mode S operation the equipment is capable of providing Enhanced Surveillance operation with its own interfaces, without the need of an additional ADLP; an Extended Squitter capability is also provided to support ADSBOUT.

The equipment is also capable of operating in conjunction with a TCAS II (V7) interrogator.

An ACC function is included in Modes 1 and 3 to facilitate pre-flight initialization and reduce User workload (when operating in association with the M910 Control Panel. Extensive BITE is provided, including Power-Up, Continuous and Initiated BIT; test results and diagnostic information are available on the control interface.



CONFIGURATION

A transponder system includes, in addition to the IFF equipment:

- A mounting tray
- Two omni antennas (Top, Bottom) for diversity operation

For applications where the antennas are not already present in the platform, we can provide a complete configuration with OEM components.

In order to support the system, we can provide a full range of solutions covering:

- Diagnostic SW (on OTS platform) for troubleshooting, calibration and Operational SW loading
- Special Test Equipment
- Automatic Test Equipment

OPERATING MODES

- MXA (1, 2, 3/A, C) i.a.w. STANAG 4193 Part I to III; ACC for Modes 1 and 3
- Mode 4 i.a.w. STANAG 4193 Part I to III, embedded or external crypto
- Mode 5 Level 1 and 2, i.a.w. STANAG 4193 Part V and VI; embedded crypto
- Mode S (Enhanced Surveillance) i.a.w. STANAG 4193 Part IV and ICAO10 (Am 77), including Extended Squitter and TCAS II (V7)

TECHNICAL SPECIFICATION

System Interface:	BUS-1553B, ARINC 429, RS 485
Sensitivity:	-78dBm 1030MHz SIF, Mode 4
Output Power:	27dBW 1090MHz
Reliability:	2000h (ARW @ 40°C)
MTBF:	>3000h (ARW @ 40°C), i.a.w. MIL-HDBK-217F
Maintainability:	Mttr < 10m LRU level
Testability:	95% fault isolation 2 SRUs
Environmental conditions:	MIL-STD-810E

Operating temperature:	-40°C to +71°C (-54°C after warmup)
Electromagnetic compatibility:	MIL-STD-461E
Dimensions:	APX 100
Weight:	< 6.5Kg (with embedded crypto)
Input power:	28VDC, i.a.w. MIL-STD-704D
Cooling:	No cooling air is required
Mounting:	Hard mounted

For more information:
airborneandspace@leonardocompany.com

Electronics Division
S.S. 17-Localita' Boschetto 67100-L'Aquila-Italy
T +39 0862 5711

This publication is issued to provide outline information only and is supplied without liability for errors or omissions. No part of it may be reproduced or used unless authorised in writing. We reserve the right to modify or revise all or part of this document without notice.

2022 © Leonardo S.p.A.

MM07883 09-19



leonardo.com

